



ISO11684 - Standard Safety Labels

All labels are available in vertical or horizontal configuration
 The 4 sizes are 38 x 68, 50 x 96, 60 x 116, 88 x 168 mm

Label Numbers

201 - 212
213 - 224
225 - 236
237 - F9

Order Form

<< Safety page



201
 Stay clear of raised boom and bucket.

202
 Secure lifting cylinder with locking device before getting in hazardous area.

203
 Attach support before getting into hazardous area.

204
 Insert safety lock before getting in hazardous area.

205
 Never tip trailer on soft ground or on a slope.

206
 Stay a safe distance from the machine.



207
 Stay clear of draft link lifting range while operating rockshaft controls.

208
 Stay clear of gate swinging area while tractor engine is running.

209
 Stay clear of raised gate unless safety lock is applied.

210
 Stay clear of articulation area while the engine is running.

211
 Do not open or remove safety shields while engine is running.

212
 Do not open or remove safety shields while engine is running.

[Printable Order Form](#)

[Return to Main Site](#)



ISO11684 - Standard Safety Labels

All labels are available in vertical or horizontal configuration
 The 4 sizes are 38 x 68, 50 x 96, 60 x 116, 88 x 168 mm

Label Numbers

- 201 - 212
- 213 - 224
- 225 - 236
- 237 - F9

Order Form

[<< Safety page](#)



213 Do not open or remove safety shields while engine is running.
 214 Do not open or remove safety shields while engine is running.
 215 Do not open or remove safety shields while engine is running.
 216 Never reach or climb into grain tank while engine is running.
 217 Put safety shield in place while grinding knives.
 218 Do not open or remove safety shields while engine is running.



219 Do not open or remove safety shields while engine is running.
 220 Do not open or remove safety shields while engine is running.
 221 Do not open or remove safety shields while engine is running.
 222 Do not step on the loading platform if PTO is connected to tractor and engine is running.
 223 Wait until machine components have completely stopped before touching them.
 224 Keep a safe distance from this machine.

[Printable Order Form](#)

[Return to Main Site](#)



ISO11684 - Standard Safety Labels

All labels are available in vertical or horizontal configuration
 The 4 sizes are 38 x 68, 50 x 96, 60 x 116, 88 x 168 mm

Label Numbers

- 201 - 212
- 213 - 224
- 225 - 236
- 237 - F9

Order Form

[<< Safety page](#)

225	226	227	228	229	230
Start engine from operator's seat only.	Shut off engine and remove key before performing maintenance or repair work.	Do not ride on platform or ladder.	Do not ride on machine except in supplied seat.	Always lock ROPS in upright position unless it has to be folded down to allow operation underneath trees or bushes.	Keep sufficient distance away from electrical power lines.

231	232	233	234	235	236
Never reach into the needle and knotter area as long as tractor engine is running with PTO connected.	Put safety shield in place while grinding knives.	Stay clear of rotating machine parts.	Stay clear of mower blade as long as engine is running.	Never reach into the crushing danger area as long as parts may move.	Stay clear of rotating auger.

[Printable Order Form](#)

[Return to Main Site](#)



ISO11684 - Standard Safety Labels

All labels are available in vertical or horizontal configuration
The 4 sizes are 38 x 68, 50 x 96, 60 x 116, 88 x 168 mm

Label Numbers

201 - 212

213 - 224

225 - 236

237 - F9

Order Form

<< **Safety page**



237
Stay clear of mower knife area as long as tractor is running with PTO connected.

238
Stay clear of header. Disengage header drive, shut off engine and remove key before servicing or unclogging header.

239
Make sure that children stay clear of mower all the time when engine is running.

240
Put safety shield in place while grinding knives.

241
Never reach into rotating auger.

242
Stay clear of hot surface.



243
To avoid possible eye injury, do not look directly into face of radar sensor while it is in operation.

244
Avoid fluid escaping under pressure. Consult technical manual for service procedures.

245
Shut off engine and remove spark plug wire before performing maintenance or repair work.

246
Never reach into pick up area as long as tractor is running with PTO connected.

f8
Carefully read Operator's Manual before handling this machine. Observe instructions and safety rules when operating.

f9
Read operator's manual.

[Printable Order Form](#)

[Return to Main Site](#)

ISO11684 STANDARD SAFETY LABELS ORDER FORM

ISO 11684 Standard Safety Signs are available in vertical or horizontal configuration.

The four sizes are 38 x 68, 50 x 90, 60 x 116, 88 x 168 mm

Please **print out** and fill in the form below then fax to (01) 620 8186. Phone us at (01) 620 8188 for further information.

LABEL NO.	SIZE mm 36 x 68 50 x 96 60 x 116 88 x 168	QUANTITY REQUIRED MINIMUM 100 ANY LABEL	CONFIGURATION V OR H VERTICAL OR HORIZONTAL

NAME:	
COMPANY:	
ADDRESS:	
PHONE:	
FAX:	
PLEASE FILL IN THE FORM AND FAX YOUR REQUIREMENTS TO US AND WE WILL QUOTE YOU BY RETURN	

Alpha Sign Nameplate & Decal Co. Ltd. Ascot House, Kylemore Park North, Kylemore Road, Dublin 10, Ireland

Tel: +353 1 620 8188 • Fax: +353 1 620 8186 • Email: info@alpha-decal.ie